

[Products](#)[Support](#)[About Us](#)[Centre](#)[Routers / MW330HP](#)[Overview](#)[Setup&App](#)[Specifications](#)

Wireless

Wireless Standards	IEEE 802.11b/g/n
Frequency	2.402-2.482GHz
WiFi Speeds	11n: Up to 300Mbps (Dynamic) 11g: Up to 54Mbps (Dynamic) 11b: Up to 11Mbps (Dynamic)
Reception Sensitivity	270M: -74dBm@10% PER 130M: -76dBm@10% PER 54M: -78dBm@10% PER 11M: -90dBm@10% PER 6 M: -94dBm@10% PER 1 M: -96dBm@10% PER
Transmission Power	<20dBm (EIRP)
Wireless Security	WPA-PSK / WPA2-PSK
Wireless Functions	Enable/Disable Wireless Radio, WDS Bridging

Hardware

Dimensions	192mm×127mm×36mm
Interfaces	3*10/100Mbps LAN Ports 1*10/100Mbps WAN Port
Button	TURBO, WPS/RESET
External Power Supply	9V/0.6A
Antenna Type	3 * 7dBi

Software

WAN Type	Dynamic IP/Static IP/PPPoE/PPTP/L2TP
Management	Access Control Local Management Remote Management
DHCP	Server
Port Forwarding	Virtual Server, UPnP, DMZ
Firewall Security	IP and MAC Address Binding
Protocols	IPv4 IPv6
Guest Network	2.4GHz Guest Network

Others

Package Contents

300Mbps High Power Wireless N Router (MW330HP)
Power Adapter
Quick Installation Guide
Ethernet Cable

Environment

Operating Temperature: 0°C~40°C (32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% Non-Condensing
Storage Humidity: 5%~90% Non-Condensing

About Us

[Corporate](#)
[Contact Us](#)
[Privacy](#)

Products

[Routers](#)
[Halo Mesh WiFi](#)
[Range Extenders](#)
[Powerline Adapters](#)
[Adapters](#)
[Switches](#)
[DSL Modems](#)
[4G Wi-Fi Routers](#)
[Mobile Wi-Fi](#)
[Smart Cameras](#)
[Access Points](#)
[xPON](#)
[Splitter](#)

Press

[Newsroom](#)
[Awards](#)

Centre A