

> CARACTERÍSTICAS

- Resistente al agua, conforme a IP65
- Carcasa de metal, antivandálica
- Tipo de tarjeta: Tarjeta EM
- Disponible para iOS y Android
- Agregar/Eliminar usuarios mediante la aplicación
- Puede establecer restricciones de tiempo para los usuarios
- Admite verificación de operaciones

> ESPECIFICACIONES

User Capacity Common User Visitor User	Hardware User: 1000 990 (PIN/Card Users) 10	APP User: 500
PIN Length	4~6 digits	
Operating Voltage Idle Current Active Current	12~18V DC ≤ 60mA ≤ 150mA	
Proximity Card Reader Radio Technology Read Range	EM 125KHz 2~6cm	
Wiring Connections	Relay output, exit button, Wiegand input/output	
Relay Adjustable Relay Output Time Lock Output Load	One (NO, NC, Common) 0~99 Seconds (5 seconds default) 2 Amp Maximum	
Wiegand Interface PIN Output	Wiegand 26~44 bits input & output (Factory default: Wiegand 26bits) 4 bits, 8bits (ASCII), 10 digits Virtual Number (Factory default: 4bits)	
Environment Operating Temperature Operating Humidity	Meets IP65 -40°C ~ 60°C (-40°F ~ 140°F) 0%RH ~ 92%RH	
Physical Color Dimensions Unit Weight Shipping Weight	Zinc-Alloy Silver & Black L142 x W48 x H22 (mm) 315g 410g	

